

TEST SICAKLIĞI	MODEL	KAPASİTE	FLEXIBLE KAPASİTESİ	SÜREKLİ MODDA GÜÇ ALIŞVERİŞİ	ΔT 35° SÜREKLİ AKIŞ ORANI	GÜÇ ALIŞVERİŞİ KESİLDİĞİNDE ΔT 35°	MAKSİMUM ÇALIŞMA SICAKLIĞI	NOMİNAL BASINÇ	FLEXIBLE NOMİNAL BASINCI	SİSTEMİN ΔT 35° GELME SÜRESİ
50°C	Solitank 200 L	170 L	12,7 L	14,9 KW	205 L/h	136 L	95°C	8 BAR	6 BAR	0 h 15'
60°C		170 L	12,7 L	18,7 KW	461 L/h	201 L	95°C	8 BAR	6 BAR	0 h 28'
70°C		170 L	12,7 L	22,7 KW	592 L/h	341 L	95°C	8 BAR	6 BAR	0 h 40'
80°C		170 L	12,7 L	28,9 KW	829 L/h	502 L	95°C	8 BAR	6 BAR	0 h 49'
50°C	Solitank Solikombi 300 L	245 L	12,7 L	16,2 KW	255 L/h	177 L	95°C	8 BAR	6 BAR	0 h 15'
60°C		245 L	12,7 L	20,9 KW	518 L/h	248 L	95°C	8 BAR	6 BAR	0 h 32'
70°C		245 L	12,7 L	24,8 KW	662 L/h	383 L	95°C	8 BAR	6 BAR	0 h 41'
80°C		245 L	12,7 L	29,7 KW	916 L/h	547 L	95°C	8 BAR	6 BAR	0 h 49'
50°C	Solitank Solikombi 500 L	454 L	18,1 L	19,8 KW	308 L/h	223 L	95°C	8 BAR	6 BAR	0 h 17'
60°C		454 L	18,1 L	24,7 KW	584 L/h	312 L	95°C	8 BAR	6 BAR	0 h 38'
70°C		454 L	18,1 L	28,6 KW	748 L/h	424 L	95°C	8 BAR	6 BAR	0 h 44'
80°C		454 L	18,1 L	33,1 KW	1028 L/h	595 L	95°C	8 BAR	6 BAR	0 h 51'
50°C	Solitank Solikombi 1000 L	1000 L	29,1 L	18,6 KW	457 L/h	313 L	95°C	8 BAR	6 BAR	0 h 26'
60°C		1000 L	29,1 L	28,6 KW	819 L/h	420 L	95°C	8 BAR	6 BAR	0 h 49'
70°C		1000 L	29,1 L	34,2 KW	1078 L/h	513 L	95°C	8 BAR	6 BAR	0 h 58'
80°C		1000 L	29,1 L	39,2 KW	1378 L/h	752 L	95°C	8 BAR	6 BAR	1 h 09'